

# RECHARGEABLE FAN

- 12" Oscillating and tilting 2-Speed Fan
- AC/DC Operated
- 6V4.5Ah Rechargeable Sealed lead-acid battery
- Long time DC power working: can work 8 hours after the battery is full
- Overdischarge & Overcharge Protection
- Built-in MP3 player
- Built-in LED Night Light

**RF-1201 RF-1202(MP3)**

Packing: 2pcs/ctn  
 Moas: 41.5\*37.5\*49.5cm  
 1\*40'HQ: 1820pcs  
 N.W.: 4.5KG G.W.: 5.5kgs



# STAND FAN



- **FS-1616**
  - ▶ Wide angle oscillation and tilting
  - ▶ 3 Speed control
  - ▶ Crossing base
  - ▶ Height adjustable
  - ▶ Motor overheating protection
- **FS-1609**
  - ▶ Wide angle oscillation and tilting
  - ▶ 3 Speed control
  - ▶ Crossing base
  - ▶ Height adjustable
  - ▶ Motor overheating protection
- **FS-1601**
  - ▶ Wide angle oscillation and tilting
  - ▶ 3 Speed control
  - ▶ Crossing base
  - ▶ Height adjustable
  - ▶ Motor overheating protection
- **FS-1617**
  - ▶ Wide angle oscillation and tilting
  - ▶ 3 Speed control
  - ▶ Crossing base
  - ▶ Height adjustable
  - ▶ Motor overheating protection

Model	Watt(w)	Airflow(cm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	dB(A@1m)
FS-1616	45	40	48x12x50	3.2	3.6	2450
FS-1609	45	40	48x12x50	3.2	3.6	2450
FS-1601	45	40	48x12x50	3.2	3.6	2450
FS-1617	45	40	48x12x50	3.2	3.6	2450

CE, RoHS, BSMI, and other certification logos. Contact information: Tel: +86-20-38520823, Fax: +86-20-47501280, Email: info@shineway.com.cn

## STAND FAN



● FS-1664

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1613

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control & lamp
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1658

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1634

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control & lamp
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40HzQ(100)
FS-1664	45	40	48x12x50	3.2	3.6	2450
FS-1613	45	40	48x12x50	3.2	3.6	2450
FS-1658	45	40	48x12x50	3.2	3.6	2450
FS-1634	45	40	48x12x50	3.2	3.6	2450



## STAND FAN



● FS-1618

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control & 120 minutes timer
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1610

- ▶ Wide angle oscillation and tilting
- ▶ 3 speed control & 120 minutes timer
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1635

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

● FS-1633

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40HzQ(100)
FS-1618	45	40	48x12x50	3.2	3.6	2450
FS-1610	45	40	48x12x50	3.2	3.6	2450
FS-1635	45	45	55x13x52	5.3	5.8	1870
FS-1633	45	45	53x13x52	5.3	5.8	1870



3rd Floor, 383/387, 100/100, Fax: +86-20-47501300  
 www.midea.com.cn  
 Email: midea@pda.com.cn info@midea.com.cn

## STAND FAN



**DIVO**



**Mosquito Repellent**

## STAND FAN



**Mosquito Repellent**

### ● FS-1607

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1646

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Crossing base
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1662

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1665

- ▶ 18" luxury stand fan, remote control is optional
- ▶ High velocity speed, powerful wind
- ▶ 3 speed control & timer
- ▶ Mosquito repellent function
- ▶ Oscillation and Tilting
- ▶ Height adjustable

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(dba)
FS-1607	45	45	53x11x42	5.3	5.8	1670
FS-1646	45	45	48x12x30	4.5	5.0	2100
FS-1662	45	45	53x11x42	5.5	6.0	1670
FS-1665	45	55	53x11.5x44	6.5	7.0	1550



### ● FS-1667

- ▶ 18" Stand fan, round base
- ▶ With timer
- ▶ 3 Speed control
- ▶ Oscillation & Tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1669

- ▶ 16" stand fan, round base
- ▶ 3 speed AS blades
- ▶ 3 speeds setting, with timer
- ▶ Pure copper motor, with overheating protection

### ● FS-1668

- ▶ 15" Stand fan, round base
- ▶ With timer
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1672

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control & timer
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection
- ▶ Mosquito repellent is optional

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(dba)
FS-1667	45	55	53x11x44	6.0	6.5	1620
FS-1669	45	55	53x11x44	6.0	6.5	1620
FS-1668	45	55	53x11x44	6.0	6.5	1620
FS-1672	45	55	50x23x45	5.5	6.0	1350



Tel: +86-20-26830333 3890265 Fax: +86-20-87672268  
 Website: www.galaxy.com.cn  
 E-mail: sales@galaxy.com.cn info@galaxy.com.cn

## STAND FAN



### ● FS-1673

- ▶ 16" stand fan, round base
- ▶ 5pcs AS blades
- ▶ 3 speeds setting, with timer
- ▶ New design on the fan guard
- ▶ Motor overheating protection
- ▶ Mosquito repellent is optional

### ● FS-1674

- ▶ 16" stand fan, round base
- ▶ 5pcs AS blades
- ▶ 3 speeds setting, with timer
- ▶ New design on the fan guard
- ▶ Motor overheating protection
- ▶ With LED lamp
- ▶ Mosquito repellent is optional

### ● FS-1680

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control & timer
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1681

- ▶ 16" stand fan, new model
- ▶ 3 speeds setting, with timer
- ▶ With shining "crystal" on switch board
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	40°HQ(pcs)
FS-1673	45	55	57x23x45	5.5	6.0	1350
FS-1674	45	55	52x23x45	5.5	6.0	1350
FS-1680	45	55	53x11x44	5.0	6.5	1650
FS-1681	45	55	73x22.5x44.5	7.0	6.5	820



## STAND FAN



### ● FS-1682

- ▶ 16" stand fan, new model
- ▶ With glass base, good looking
- ▶ 3 speeds setting
- ▶ With LED lamp

### ● FTD-1401

- ▶ 14" stand fan, and table fan
- ▶ 5pcs AS blades
- ▶ 3 speeds setting
- ▶ Pure copper motor with overheating protection

### ● FS-1871

- ▶ 18" Stand fan, round base
- ▶ 5pcs AS blades
- ▶ With timer
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1807

- ▶ Wide angle oscillation and tilting
- ▶ 3 Speed control
- ▶ Round base
- ▶ Height adjustable
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	40°HQ(pcs)
FS-1682	50	55	102.5x18.5x44	7.0	8.5	975
FTD-1401	45	50		6.5	7.0	1150
FS-1871	55	60	90.5x23x90.5	6.5	7.0	1150
FS-1807	55	60	90.5x23x90.5	6.5	7.0	1150



Tel: +86-20-38320812 32893205 Fax: +86-20-47501200  
 Web: www.victorfan.com  
 E-mail: victorfan@victorfan.com.cn info@victorfan.com

## STAND FAN



Mist Fan



### ● FS-1688

- ▶ 16" stand fan, with humidifier function
- ▶ 1.5L water tank, can work 12-15 hours
- ▶ Base with pulley, easily for moving
- ▶ Motor with overheating protection

### ● FS-1690

- ▶ 16" stand fan, with humidifier function
- ▶ 3 Speed control
- ▶ Height adjustable
- ▶ Motor with overheating protection


### ● FS-1649

- ▶ 16" stand fan, round base
- ▶ Banana PP blade
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1648

- ▶ 16" stand fan, round base
- ▶ Metal blade
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	407HQ(pcs)
FS-1688	50	25	57x30x45	6.5	9.5	460
FS-1690	50	55	106x22 6x48.5	8.0	7.0	594
FS-1649	45	25	51x13x51	5.5	6.0	1500
FS-1648	45	50	48x14x48	6.0	7.0	1660



## STAND FAN



### ● FS-1804

- ▶ 18" stand fan, round base
- ▶ Banana PP blade
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1808

- ▶ 18" stand fan, round base
- ▶ Banana PP blade
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● FS-1809

- ▶ 18" stand fan, round base
- ▶ Banana PP blade
- ▶ 3 speed control
- ▶ Oscillation & tilting
- ▶ Height adjustable
- ▶ Motor overheating protection

### ● IF3-18

- ▶ 18" stand fan, 3 inf fan
- ▶ Round base
- ▶ 3 speeds setting
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	407HQ(pcs)
FS-1804	50	60	50x14x50	5.5	6.0	1600
FS-1808	50	60	50x14x50	5.5	6.0	1600
FS-1809	50	60	50x14x50	5.5	6.0	1600
IF3-18	80	80	54x16x51	7.8	8.8	1290



3# 4020-3833683 0090395 Fax: 86-24-4791900  
 Web: www.midea.com.cn  
 E-mail: midea@pch.com.cn info@pch.com.cn

## METAL FAN



### FES-45

- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade, Powerful wind
- ▶ Height adjustable
- ▶ Motor overheating protection

### FD-40M

- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade, Powerful wind
- ▶ Height adjustable
- ▶ Motor overheating protection

### FD-40MC

- ▶ 10" metal stand fan
- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade
- ▶ Motor overheating protection

### FTD-40M

- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade, Powerful wind
- ▶ Height adjustable
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
FES-45	170	90	37x33x45	10.1	11.2	816
FD-40M	50	60	46.6x16x59.5	7.0	8.0	1518
FD-40MC	50	60	51x16x53	7.2	8.2	1288
FTD-40M	50	60	36x29x35	3.5	4.0	2362



## METAL FAN



### IF-20A (20"20"130")

- ▶ Full metal body
- ▶ Powerful motor & strong wind
- ▶ 3 years guarantee

### IF-20C (20"20"130")

- ▶ Full metal body
- ▶ Powerful motor & strong wind
- ▶ 3 years guarantee

### IF-18

- ▶ Full metal body
- ▶ Powerful motor & strong wind
- ▶ 3 years guarantee

### WF-26 (26"10")

- ▶ Full metal body
- ▶ Powerful motor & strong wind
- ▶ 3 years guarantee

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
IF-20A	160	250	71x26x71	16.0	19.0	489
IF-20C	160	250	71x26x71	16.0	19.0	489
IF-18B	100	200	64x17x51.5	11.8	13.2	1185
WF-26	130	250	73.6x17x66	8.0	9.0	958



## METAL FAN



### ● FT-25MA (10"/12"/16")

- ▶ 10" metal table fan
- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade
- ▶ Motor overheating protection

### ● FT-30MB (10"/12"/16")

- ▶ 12" metal table fan
- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade
- ▶ Motor overheating protection

### ● FT-40MC (10"/12"/16")

- ▶ 10" metal table fan
- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade
- ▶ Motor overheating protection

### ● FT-40MD (10"/12"/16")

- ▶ 10" metal table fan
- ▶ Wide angle oscillation and tilting
- ▶ Aluminum blade
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
FT-25MA	30	35	30.5x21x31	2.5	3.2	5630
FT-30MB	35	40	35x21x35	2.9	3.5	2774
FT-40MC	50	50	46x21x46	3.9	4.6	1925
FT-40MD	50	50	46x21x46	3.9	4.6	1925



## METAL FAN



### ● IF-401P

- ▶ 4" metal floor fan
- ▶ Blowing up and down
- ▶ Motor overheating protection

### ● IF-1201C

- ▶ 12" metal floor fan
- ▶ Blowing up and down
- ▶ Powerful wind
- ▶ Motor overheating protection

### ● IF-1601C

- ▶ 16" metal floor fan
- ▶ Blowing up and down
- ▶ Powerful wind
- ▶ Motor overheating protection

### ● IF-1802C

- ▶ 18" metal floor fan
- ▶ Blowing up and down
- ▶ Powerful wind
- ▶ Motor overheating protection

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
IF-401P	15	10	45x20.5x43	0.54	1.0	23310
IF-1201C	50	60	49x20.5x43	3.6	4.6	1679
IF-1601C	100	120	51x20x51	4.8	5.8	1265
IF-1802C	130	150	57x20x56	5.4	6.4	1084



Tel: +86-20-26830000 3895085 Fax: +86-20-8761288  
 Web: www.midea.com.cn Email: midea@china.midea.com



## TABLE FAN



### ● FT-40A

- ▶ 10" table fan
- ▶ Wide angle oscillation
- ▶ 3 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard



### ● FT-30A ● FT-23A

- ▶ 12" table fan
- ▶ Wide angle oscillation
- ▶ 2 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard



### ● FT-40B

- ▶ 10" table fan
- ▶ Wide angle oscillation
- ▶ 3 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard



### ● FT-30B ● FT-23B

- ▶ 12" table fan
- ▶ Wide angle oscillation
- ▶ 2 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
FT-40A	45	40	44x19x44.5	2.5	3.2	1800
FT-30A/FT-23A	35/25	30/25	35.5x19x37.5/28x18x31.5	2.1/1.4	2.5/1.7	2770/4122
FT-40B	45	40	44x19x44.5	2.5	3.2	1800
FT-30B/FT-23B	35/25	30/25	35.5x19x37.5/28x18x31.5	2.1/1.4	2.5/1.7	2770/4122



## TABLE FAN



### ● FT-40C

- ▶ 10" table fan
- ▶ Wide angle oscillation
- ▶ 3 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard



### ● FT-30C ● FT-23C

- ▶ 12" table fan
- ▶ Wide angle oscillation
- ▶ 2 Speed control
- ▶ Motor overheating protection
- ▶ Detachable base
- ▶ Mesh net guard



### ● FT-1613

- ▶ 10" table fan
- ▶ Wide angle oscillation
- ▶ 3 Speed control
- ▶ Motor overheating protection
- ▶ Metal blade & golden ring



### ● FT-1614

- ▶ 10" table fan
- ▶ Wide angle oscillation
- ▶ 3 Speed control
- ▶ Motor overheating protection
- ▶ Metal blade & golden ring

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40"HQ(pcs)
FT-40C	45	40	44x19x44.5	2.5	3.2	1800
FT-30C/FT-23C	35/25	30/25	35.5x19x37.5/28x18x31.5	1.4/2.1	1.7/2.5	4122/2771
FT-1613	45	55	43x14x55	2.5	3.0	1800
FT-1614	45	55	48x14x48	2.5	3.0	1800





## WALL FAN



### WF-1601

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillation
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1602

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillation
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1607

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillator
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1615

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillator
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1603

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillation
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1605

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillation
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1804

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillator
- ▶ Motor overheating protection
- ▶ Strong air delivery



### WF-1803

- ▶ 18" wall fan, 3 speed setting
- ▶ Wide angle oscillator
- ▶ Motor overheating protection
- ▶ Strong air delivery

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40Hz(dB(A))
WF-1601	45	40	44x18x44	3.2	3.8	2000
WF-1602	45	40	44x18x44	3.2	3.8	2000
WF-1603	45	40	44x18x44	3.2	3.8	2000
WF-1605	45	40	44x18x44	3.2	3.8	2000



## WALL FAN

Model	Watt(w)	Airflow(cfm/min)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40Hz(dB(A))
WF-1607	45	40	48x18x44	3.2	3.8	2000
WF-1615	45	40	48x18x44	3.2	3.8	2000
WF-1804	55	50	52x14x52	3.5	4.0	1100
WF-1803	55	50	52x14x52	3.5	4.0	1100



TEL: +86-351-2822002 3290300 Fax: +86-351-211712 280  
 WWW: www.midea.com.cn  
 E-mail: midea@public.midea.com.cn midea@vip.sina.com

## TOWER FAN



### ● FS-2901

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2902

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2910

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2903

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	40HQ(pcs)
FS-2901	45	25	77x16x22	3.4	3.9	2960
FS-2902	45	25	77x16x22	3.4	3.9	2960
FS-2910	45	25	78x17.5x22	3.4	3.9	2960
FS-2903	55	25	77x16x24	3.5	4.0	2320



## TOWER FAN



### ● FS-2904

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2911

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2913

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent



### ● FS-2914

- ▶ 29" tower fan
- ▶ 3 speed control & 7.5 hours timer
- ▶ Wide angle oscillation
- ▶ With Remote control
- ▶ Silent

Model	Watt(w)	Airflow(cbm/min)	Dimension(cm)	N.W(KG)	G.W(KG)	40HQ(pcs)
FS-2904	45	25	79.5x18.5x22	3.4	3.9	2164
FS-2911	45	25	77x16x22	3.4	3.9	2560
FS-2913	45	25	78x17x22	3.3	3.8	2960
FS-2914	45	25	78x19x22	3.5	4.0	2188




TEL: +86-20-38534823 33903365 Fax: +86-20-87101280  
 WWW: www.midea.com.cn  
 E-mail: midea@china.midea.com.cn info@midea.com.cn

## CEILING FAN



CF-56P



CF-56C



CF-56R



Golden Ring



Golden Ring

CF-62M

**Best in quality & durable in design**  
 An "E" Grade insulation to protect from electric shock  
 Silicon steel lamination  
 Double sealed ball bearings & low noise  
 Aerodynamically designed blades for high velocity air  
 High energy efficiency ratio and low temperature(75K)

Model	Watt(w)	Air flow(cfm/min)	Energy Efficiency Ratio	Temperature (K)	Rotor Size (mm)
CF-66P	63	270	3.25	75	194x12.8
CF-66C	75	269	3.55	72	171x13.8
CF-62M	66	314	3.3	75	194x14.4
CF-56H	81	258	3.15	73	194x12.0

## CEILING FAN



CF-56H



CFN-60B



CF-56H-1

CFN-60B-1



Golden Ring

**Best in quality & durable in design**  
 An "E" Grade insulation to protect from electric shock  
 Silicon steel lamination  
 Double sealed ball bearings & low noise  
 Aerodynamically designed blades for high velocity air  
 High energy efficiency ratio and low temperature(75K)

Model	Watt(w)	Air flow(cfm/min)	Energy Efficiency Ratio	Temperature (K)	Rotor Size (mm)
CF-56H	80	330	3.66	70	194x16.8
CF-56H-1	99	366	3.67	75	194x18.0
CFN-60B-1	67	316	3.25	70	194x17.4
CFN-60B	97	316	3.25	70	194x17.4

## CEILING FAN



CFN-56A



CFN-60D



CFN-56E



CFN-60C

**Best in quality & durable in design**  
 An "E" Grade insulation to protect from electric shock  
 Silicon steel lamination  
 Double sealed ball bearings & low noise  
 Aerodynamically designed blades for high velocity air  
 High energy efficiency ratio and low temperature(75K)

Model	Watt(w)	Airflow(cbm/min)	Energy Efficiency Ratio	Temperature (K)	Rotor Size (mm)
CFN-56A	80	248	3.1	75	175x15.0
CFN-60D	100	270	2.7	75	194x12.0
CFN-56C	100	270	2.7	75	194x12.0
CFN-56E	80	248	3.1	75	175x15.0

## CEILING FAN



CF-56W



CFL-56N



CFL-56P



CF-56T

**Best in quality & durable in design**  
 An "E" Grade insulation to protect from electric shock  
 Silicon steel lamination  
 Double sealed ball bearings & low noise  
 Aerodynamically designed blades for high velocity air  
 High energy efficiency ratio and low temperature(75K)

Model	Watt(w)	Airflow(cbm/min)	Energy Efficiency Ratio	Temperature (K)	Rotor Size (mm)
CF-56G	83	270	3.25	75	194x12.6
CFL-56N	72	292	3.8	75	175x13.6
CFL-56P	83	270	3.25	75	194x12.6
CF-56T	100	315	3.15	75	194x16.0



Tel: +91-20-26832003 2090300 Fax: +91-20-4750100  
 Email: info@lumini.com Website: www.lumini.com

## CEILING FAN



CF-56J



CFN-56G-1



CFN-56K-1

**Best in quality & durable in design**  
**An "E" Grade insulation to protect from electric shock**  
**Silicon steel lamination**  
**Double sealed ball bearings & low noise**  
**Aerodynamically designed blades for high velocity air**  
**High energy efficiency ratio and low temperature(75K)**



CFN-56K



CFN-56G

Model	Watt(w)	Airflow(L/min)	Energy Efficiency Ratio	Temperature (K)	Rotor Size (mm)
CF-56J	83	278	3.26	76	164x12.6
CFN-56K	82	269	3.26	75	171x16.6
CFN-56G	78	207	2.96	70	171x14.4
CFN-56K-1	82	269	3.26	75	171x14.4
CFN-56G-1	78	207	2.96	70	171x16.6

## MOTOR



BOX FAN MOTOR

71X12/14/16/18MM



BOX FAN MOTOR

82X16/18MM



BOX FAN MOTOR

75X14/16/18MM




MOTOR WITH OCLLATION GEAR BOX

71X12/14/16/18/20MM




ORBIT FAN MOTOR

75X23MM



Coil




Steel Sheet



MOTOR WITH OCLLATION GEAR BOX

75X12/14/16/18/20/22/25/27MM



Tel: +91-20-2682062 2090300 Fax: +91-20-4750100  
 www.motorindia.com  
 E-mail: motorindia@motorindia.com info@motorindia.com

## DECORATIVE CEILING FAN



MF52E-4W3B

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 3 lamps



MF48F-5W3SC

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 5 wooden blades, 3 lamp



MF42-4C3TD

- ▶ 42" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 3 lamps



MF52G-4W3SG

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 3 lamps

Model	Watt(w)	Air flow(cfm/m3/hr)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40HQ(pcs)
MF48F-5W3SC	70	90	54x23x20	5.0	5.5	2300
MF52E-4W3B	70	90	50.5x32x20	5.5	6.0	1920
MF42-4C3TD	55	40	42x18.5x21	5.0	5.5	4200
MF52G-4W3SG	60	90	52.5x27x24.5	7.0	7.8	1950

## DECORATIVE CEILING FAN



MF52H-5W1TC

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 5 wooden blades, 1 lamp



MF52J-4W4SH

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 4 lamps



MF52K-5C5L

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 5 wooden blades, 5 lamps



MF48-4W1L

- ▶ 48" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 1 lamp

Model	Watt(w)	Air flow(cfm/m3/hr)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40 HQ(pcs)
MF52H-5W1TC	70	90	50.5x32x20	5.5	6.0	1650
MF52J-4W4SH	70	90	54x29x20	5.0	5.5	2300
MF52K-5C5L	60	90	54x28x20	6.5	7.0	1780
MF48-4W1L	70	90	55x25x22	5.5	6.0	2100



Tel: +86-20-38833983 3393395 Fax: +86-20-87501390  
 www.midea.com/en/eng  
 E-mail: midea.en@pccw.com.cn midea@pccw.com.cn

## DECORATIVE CEILING FAN



MF56-4P1L

- ▶ 60" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 plastic blades, 1 lamp



MF52-4W1L

- ▶ 52" Ceiling fan, decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by regulator
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 1 lamp



MF48-3W1L

- ▶ 48" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by regulator
- ▶ Soft wind with silent operation
- ▶ 3 wooden blades, 1 lamp



MF52-4W

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by regulator
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades

Model	Watt(w)	Airflow(cfm/mn)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40°HQ(pcs)
MF52-4W1L	70	50	60, 7x25x29, 2	6, 5	7, 5	1360
MF56-4P1L	80	66	0 1x24, 5x22, 5	5, 0	5, 5	2060
MF48-3W1L	60	50	58x25x22	5, 0	5, 5	2100
MF52-4W	70	55	60, 7x28x29, 2	6, 0	6, 8	1360

## DECORATIVE CEILING FAN



MF52D-5W1TE

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 5 plastic blades, 1 lamp



MF52B-5W1RC

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 5 wooden blades, 1 lamp



MF42A-4W1TF

- ▶ 42" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 4 wooden blades, 1 lamp



MF52C-6P6SI

- ▶ 52" Ceiling fan decorative/cooling/lighting
- ▶ Two-side operation, clockwise and anti-clockwise
- ▶ Speed and lamp controlled by pull
- ▶ Soft wind with silent operation
- ▶ 6 plastic blades, 6 lamps

Model	Watt(w)	Airflow(cfm/mn)	Dimension(cm)	N.W.(KG)	G.W.(KG)	40°HQ(pcs)
MF52D-5W1TE	70	50	54x28x20	6, 0	6, 5	1660
MF42A-4W1TF	70	40	41x23x25	5, 0	5, 5	2300
MF52B-5W1RC	60	50	51x22x25	6, 0	6, 5	1660
MF52C-6P6SI	70	50	65x29x25	7, 0	7, 6	1660



Tel: +86-20-38030873 3090305 Fax: +86-20-87501390  
 www.midea.com.cn  
 E-mail: midea@pccw.com.cn info@midea.com.cn